



## DESCRIPTION

Acrylic waterborne matt paint.  
 \* Smooth appearance, washable.  
 \* Interior.

## FIELD OF USE

All interior work.

## TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- White color.
- Dilution: up to 10% depending on the support.
- Spreading-rate : 10 to 12m<sup>2</sup>/L . Soit 7 à 8m<sup>2</sup>/Kg, depending on the porosity of the support, in accordance with ISO 23811 (2009).
- Density : 1,54 +/- 0,05 at 25°C, Complies with NM ISO 2811-1 (2008).
- Viscosity : 114 +/- 5 KU at 25°C, Complies with ASTM D561 (1997).

AFNOR classification (NF T36-005): Family I class 7b2.  
 C.O.V. classification (directive 2004/42 / CE):  
 EU limit value of this product Category A / a: 10 g / l (2010).  
 This product contains a maximum of 5g / l VOC. EU  
 ECOLABEL: FR / 044 / YY.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Limit of application: Do not apply on condensing or frozen substrates, at temperatures below 5 ° C and above 35 ° C, nor at relative humidity above 65%.

## APPLICATION DETAILS OF USAGE

Application tool: anti-drip roller, brush. Application conditions in accordance with the NFP standard 74-201 (DTU 59.1).  
 The preparation of the base (new or old, covered or not) must be done in accordance with standard NF P 74-201 (DTU 59.1). Prior recognition is necessary to determine the nature of the preparations and the possible impression.

## DILUTION & ADVICE

1st coat diluted with 10% water if necessary.  
 Avoid wasting paint, estimate how much paint you need.  
 Close unfinished pots so that the paint can be reused.  
 Reusing paint is a good way to reduce the environmental impact of products over their entire life cycle.  
 Estimate the quantity needed before purchase in order to optimize cost and waste: 10L +/- 60m<sup>2</sup>  
 For information on disposal methods, contact the local authorities.

## DRYING TIME

Drying at 20 ° C and 65% relative humidity:  
 \*Dust dry: 30 min.  
 \*Dry: 45 min.  
 \*Interval between coats: minimum 4 hours.

## RECOMMENDED SYSTEM

- INTERIOR (contact us):

SYSTEM	NUMBER OF COATS
COLOPRIM PLUS(*)	1
ACRYMAT	2

(\*) On porous surfaces: first apply a coat of COLOFIX.

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from direct sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

## PACKAGING

3L, 10 L.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°32.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.  
 This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees.  
 Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001