



DESCRIPTION

AMANMAT is an ecological paint in a waterborne with a smooth matte appearance, with a high resistance to washability and yellowing. AMANMAT has a very low odor upon application.

FIELD OF USE

Mat paint for all interior wall surfaces (living rooms).

TECHNICAL CHARACTERISTICS

- Aspect : Mat.
- Brilliance: conforms to NM ISO 2813 (2005).
- Color: White, it can be tinted with our Tints 2000 (do not exceed 5%).
- Spreading - rate : 8 to 10 m²/kg.
- Density : 1,43 +/- 0,05 at 25°C, complies with NM ISO 2811-1 (2008).
- Viscosity : 360 +/- 50 P at 25°C.

SURFACE PREPARATION

The work must be done in accordance with the NF DTU59.1 standard and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Dilution: 5 to 10 % of water for roller and brush.
Limits of application: Do not apply on condensing or frozen support, by temperature lower than 5°C, and higher than 35°C, nor by relative humidity higher than 65%.

APPLICATION DETAILS OF USAGE

Application equipment: Roller or brush or spray gun. A preliminary recognition is necessary to determine the nature of the preparations and the impression.

DILUTION & ADVICE

Apply the 1st coat of AMANMAT diluted to 10% with a roller or brush. Avoid wasting paint, estimate the amount of paint you need.
Close the unfinished cans so that you can reuse the paint.
Reusing paint is a good way to reduce the environmental impact of products over their entire life cycle.
After 4 hours of drying, apply the 2nd coat of AMANMAT diluted at 5%.
Cleaning of equipment: With water, immediately after use.

DRYING TIME

Drying at 20°C and 65% relative humidity:
*Dust free: 30 min.
*Dry: 1 hour.
*Interval between coats: minimum 4 hours.

RECOMMENDED SYSTEM

- INTERIOR (consult us):

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
AMANMAT	2

STORAGE

The product can be stored for up to 2 years under good storage conditions, away from sunlight and frost, in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

4kg, 15kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°309.

Edition : February 2022 by Colorado 02/22 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001