



DESCRIPTION

Vinyl paint for standard work.

FIELD OF USE

Recommended for application on exterior and interior walls.

TECHNICAL CHARACTERISTICS

- Aspect : Mât.
- Colors : White, it can be tinted with our Tints 2000.
- Spreading-rate : 6 to 8 m²/kg depending on the porosity of the support.
- Density : 1,74 +/- 0,05 at 25°C, complies with standard NM ISO 2811-1 (2008).
- Viscosity : 400 +/- 50 Poise at 25°C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care. Prior recognition is necessary to determine the nature of the preparations and the possible impression.

CONDITIONS AND METHODS OF APPLICATION

Application limit: Do not apply on condensing or frozen support, at temperatures below 5 ° C and above 35 ° C, nor at relative humidity above 65%. Apply the 1st coat of ANFA VINYL diluted at 15% with the roller or brush. Avoid wasting paint, estimate how much paint you need. Close unfinished pots so that the paint can be used again. Reusing paint is a good way to reduce the environmental impact of products over their entire life cycle. After 4 hours of drying apply the 2nd coat diluted to 5%. Application material: Roller or brush or gun. Equipment cleaning: With water, immediately after use.

APPLICATION DETAILS OF USAGE

Dilution: 15% water in the first coat, 5 to 10% water in the second coat.

DRYING TIME

- *Dust dry: 30 min.
- *Dry: 1 hour.
- *Interval between coats: 4 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
ENDUIT P66 or P77	2
ANFA VINYL	2

■ EXTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM	1
ENDUIT FACADE P20 or P10	2
ANFA VINYL	2

STORAGE

The product can be stored for up to 2 years under good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

1 kg, 5 kg, 10kg, 30 kg, 45 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°300.

Edition : September 2021 by Colorado 09/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001