



DESCRIPTION

One-component oven-baked primer based on alkyd-melamine and anticorrosion pigments, Primer without sanding, can be applied wet on wet, apply on well degreased and sanded metal substrates has very good adhesion and excellent filling power it has a good adhesion and good filling power.

FIELD OF USE

Oven Primer is an undercoat for oven paint for industrial use, gas cylinders, office furniture, signage and the automotive industry.

TECHNICAL CHARACTERISTICS

- Aspect : Matt satin.
- Color : A choice.
- Density : 1,50 ± 0,05 depending on the color.
- Viscosity : 180 ± 20 sec CF4 at 25°C.
- Volume solids : 60 ± 2 (%). Theoretical
- Spreading-rate : 6.6/kg/60µm.
- Grip: class 0.
- Persoz pendulum hardness: ≥180sec. Impact
- resistance: ≥50cm.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

APPLICATION DETAILS OF USAGE

Dilution: Thinner in oven D77 up to 20%.

DRYING TIME



Evaporation time at 20 ° C : 10min.



Oven drying (steaming) (120 ° to 130 ° C) : 20 to 30 min.

STORAGE

The product can be stored for up to 1 year under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

25 kg, 200 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 109.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001