



## DESCRIPTION

CERAMICA allows you to cover the old tiling of your interior and exterior surfaces. It hides the flaws of your irregular walls.

## FIELD OF USE

CERAMICA is applied directly, without primer on tiling, plaster, sanded paints, earthenware. Very good adhesion. It gives a smooth and regular appearance to your finishing paints.

## TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Color : White.
- Spreading-rate : 3 to 4 m<sup>2</sup>/kg depending on the irregularity of the support.
- Density : 1,55 +/- 0,05 at 25° C.
- Viscosity : 2400 +/- 500 poises at 25° C.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Mix well before application.  
Apply on a clean, seine and dry surface. Apply a first coat with a coating knife.  
24 hours after applying the 2nd coat. Let dry. For a smoother surface, apply 1 to 2 coats of COLOSTOP or SP88 plaster.  
Apply 1 to 2 coats of finish paint.  
Application limit: Do not apply on condensing, frozen substrates, at temperatures below 5 ° C and / or relative humidity above 65%.

## APPLICATION DETAILS OF USAGE

Dilution: Product ready to use.

## DRYING TIME

At 20 ° C and 65% humidity:  
\* Dry to touch: +/- 6 hours.  
\* Recoatable: +/- 24 hours.

## RECOMMENDED SYSTEM (contact us)

### ■ INTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT CERAMICA	2
COLOSTOP or SP88	1 to 2
FINISHING PAINT	2

### ■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT CERAMICA	2
ENDUIT P10	1 to 2
COLOPRIM or COLOFIX	1
FINISHING PAINT	2

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

5 kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 11.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001