



FR/044/056



DESCRIPTION

White undercoat essential before the application of finishing paints in waterborne. Allows to standardize the support in order to obtain a beautiful finish.
Inside and outside.

FIELD OF USE

Undercoat essential before the application of paints in waterborne essential especially on raw supports before painting of finishing products.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Color : White.
- Spreading-rate : 8 to 10 m²/L depending on the substrate, conforms to ISO 23811 (2009).
- Density : 1,35 +/- 0,05 Kg/L at 25°C, Complies with NM ISO 2811-1 (2008).
- Dry extract : 55 % in weight + / - 2%, Compliant with ISO3233-3 (2015).
- Viscosity : 100 +/- 5 KU at 25°C, Complies with ASTM D561 (1997).
AFNOR classification (NF T36-005): Family I class 7b2. C.O.V. classification (directive 2004/42 / CE): EU limit value of this product category A / g: 15g / l (2010). This product contains a maximum of 9.6 g / l VOC.
EU ECOLABEL: FR / 044/056.

SURFACE PREPARATION

The work must be done in accordance with the NF DTU59.1 standard and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Application limit: Do not apply on condensing or frozen support, at temperature below 5 ° C nor at relative humidity above 65%.

APPLICATION DETAILS OF USAGE

Application tool: anti-drip roller. Application conditions in accordance with standard NFP 74-201 (DTU 59.1).
The preparation of the base (new or old, covered or not) must be done according to standard NF P 74-201 (DTU 59.1) Prior recognition is necessary to determine the nature of the preparations and the possible impression.

DILUTION & ADVICE

1st coat diluted with 10% water if necessary. Avoid wasting paint, estimate how much paint you need. Close any unfinished jars so that the paint can be reused.
Reusing paint is a good way to reduce the environmental impact of products over their entire life cycle.
Estimate the quantity needed before purchase in order to optimize cost and waste: 10L +/- 100 m². For information on disposal methods, contact the local authorities.

DRYING TIME

Drying at 20 ° C and 65% relative humidity:
* Dry to touch: 30 minutes.
* Recoatable: 4 hours.

RECOMMENDED SYSTEM (contact us)

■ INTERIOR EXTERIOR :

SYSTEM	NUMBER OF COATS
COLOFIX	1
FINISHING PAINT	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

3 L, 10 L.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N ° 193.

Edition : October 2021 by Colorado 10/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001