



## DESCRIPTION

COLOFONDO is an undercoat for decoration products (Florence, Arabesk, Sicilia, Touareg and Rimal) based on acrylic copolymers.

## FIELD OF USE

COLOFONDO is applied on interior and exterior masonry cladding, woodwork and plaster, it has good whiteness and high covering power.

## TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colors : Delivered in white FONDO ATF (for Florence, Touareg, Arabesk and Rimal) or tinted (for Sicilia, Touareg and Rimal) the colors available are cream, burgundy, gray, red, blue, green, brown, pink and beige.
- Spreading-rate : 9,6 to 11,2 m<sup>2</sup>/L depending on the porosity of the support.
- Density : 1,66 +/- 0,05 at 25°C.
- Viscosity : 130 +/- 5 KU's with a Krebs Stormer viscometer at 25 °C.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

COLOFONDO is applied with an anti-drip roller or a brush without any risk of rework or connection.

## APPLICATION DETAILS OF USAGE

From 10 to 15% water.

## DRYING TIME

- Drying at 20 ° C and 60% humidity:
- \* Dust free: 15 min.
  - \* Dry: 60 mn.
  - \* Recoatable: 12 hours.

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

1,6 L.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 26.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001