



DESCRIPTION

An aqueous dispersion of a vinyl copolymer specially designed for the manufacture of Scratching Glue.

FIELD OF USE

Griffi Coating Glue is a glue used in the preparation of a mixture with grains of sand and marble dust to obtain Griffi. It gives good grip, excellent stability and good resistance to water and weathering. Griffi coating is suitable for all spaces exposed to the exterior (facades).

TECHNICAL CHARACTERISTICS

- Aspect : Liquid and transparent product.
- Colors : Transparent, can be tinted with Shade 2000.
- Mix spreading-rate : 2 to 3 m²/Kg.
- Density : de 1,05 à 1.10 at 20°C.
- Viscosity : 600 +/- 100 P at 25°C.

SURFACE PREPARATION

Les travaux doivent se faire conformément à la norme NF DTU59.1 et seront réalisés avec le plus grand soin.

CONDITIONS AND METHODS OF APPLICATION

Pour une application facile et un rendement optimal, la surface doit être propre, saine et sèche. Si le support est humide; éliminer la source d'humidité et appliquer en impression une couche de COLOGRIFFI diluée environ 100% avec l'eau. Appliquer le mélange avec la taloche inox puis lisser le support avec une taloche spéciale. Après environ 10 heures de séchage, appliquer une couche de COLOGRIFFI pour la protection et la lavabilité.

APPLICATION DETAILS OF USAGE

Détails de la préparation du mélange (Formule pour 100 kg de Griffé) :

- * Prendre 4% de la Colle « COLOGRIFFI ».
- * Rajouter 12% d'eau minimum.
- * Rajouter au mélange 80% de poussière de marbre et 4% de grains de sable jusqu'à l'obtention d'un mélange homogène.

STORAGE

Le produit peut être stocké jusqu'à 2 ans dans de bonnes conditions de stockage à l'abri du soleil et du gel dans son emballage fermé d'origine. Il est néanmoins recommandé d'agiter le produit avant son utilisation.

PACKAGING

1 kg, 4 kg et 30 kg.

HEALTH & SAFETY

Des informations de santé, de sécurité et des précautions d'emploi sont détaillées sur la fiche de données de sécurité N° 36.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001