



DESCRIPTION

Glossy paint based on modified glycerophthalic resins. Cololac+ can be applied indoors on all usual properly prepared building substrates. Complies with NM 03.3.255 and NM 03.3.256.

FIELD OF USE

Interior surfaces.

TECHNICAL CHARACTERISTICS

- Aspect : Gloss.
- Colors : according to color chart. Can be dyed with Colopâte.
- Spreading-rate : 8 à 9 m²/Kg .
- Density : 1,35 ± 0.05 at 25°C (White).
- Dry extract : 72 % ± 2%.
- Viscosity : 100 ± 5 KU at 25°C with the Krebs viscometer.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

APPLICATION PROPERTIES

Application limit: Do not apply on condensing or frozen substrates, at temperatures below 5 ° C, or at relative humidity above 65%.

APPLICATION DETAILS OF USAGE

D 66 (White Spirit).

DRYING TIME

- Drying at 20 ° C and 60% humidity:
- *Dust free: 3 hours.
- *Dry: 8 hours.
- *Recoatible: Minimum 24 Hours.

RECOMMENDED SYSTEM

- INTERIOR (Hydraulic supports: contact us)

SYSTEM	NUMBER OF COATS
FORMORAL or COLOFIX	1
ENDUITPAT P66 or COLENDUIT	2
FORMORAL	1
COLOLAC+	2

STORAGE

The product can be stored for up to 2 years under good storage conditions away from sunlight and frost in its original closed packaging. However, it is recommended to shake the product before use.

PACKAGING

0,5 kg, 1 kg, 5 kg 15kg, 20 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N°12.

Edition : February 2025 by Colorado 02/25 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001, ISO 45001 and ISO 27001