



DESCRIPTION

Finishing putty to even out sanding marks or irregularities on the surface of the bodywork.

FIELD OF USE

The Colomastic is applied on: Metal, Wood.

CHEMICAL BASIS

Thixotropic nitro-cellulose finishing putty.

GENERAL CHARACTERISTICS

- * Hides sanding marks, scratches and irregularities.
- * Additional layer on an already prepared body part.

PROPRIETES PHYSIQUES

- Relative density : 1.5 ± 0.05 at 25°C .
- Dry extract weight : $80 (\%) \pm 2$.
- Color: Beige, White, Gray and Red.
- Spreading-rate : depending on the condition of the substrate and the thickness.

APPLICATION DETAILS FOR USAGE

- Mixing ratio: Ready to use.

PACKAGING

0,5 Kg, 1 Kg.

DRYING TIME



Evaporation time at 20°C 5 _ 10min.



Drying time at 20°C 20 _ 30min.

CONDITIONS AND METHODS OF APPLICATION



Application material: Body knives.



Drying time at 20°C : 20 to 30min.



Sanding: Dry sand only

STORAGE

The product can be stored for up to 1 year under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N°76.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001