



## DESCRIPTION

COLOTITANE is a velvety matt emulsion paint based on acrylic copolymers, specially designed for new exterior work, however it is very popular for interior decoration. COLOTITANE is distinguished by very good whiteness, very high opacifying power, very easy to apply, high yield even on too absorbent substrates and very good washability.

## FIELD OF USE

Recommended for application on exterior and interior concrete, plaster and plaster walls.

## TECHNICAL CHARACTERISTICS

- Aspect : Velvety mast.
- Colors : Supplied in white and can be tinted with Shades 2000.
- Spreading-rate : 7 to 9 m<sup>2</sup> / Kg per coat depending on the porosity of the support, in accordance with ISO 23811 (2009).
- Density : 1.65 ± 0.05 at 25 °C, conforming to NM ISO 2811-1 (2008).
- Viscosity : 400 ± 50 poises at 25 °C at Brookfield.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Recommended material: Brush or roller. Also airless. Do not apply on condensing or frozen substrates at temperatures below 5 °C nor at humidity above 70%.

## APPLICATION DETAILS OF USAGE

Dilution : water.

## DRYING TIME

- Drying at 20 °C and 60% humidity:
- \* Dust free: 15 min
  - \* Dry: 30 min
  - \* Interval between coats: 3 hours minimum.

## RECOMMENDED SYSTEM (Consult us)

### ■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10	1
COLOPRIM or COLOFIX	1
COLOTITANE	2

### ■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505, SP88	2
COLOSTOP	1
COLOFIX	1
COLOTITANE	2

## LABELS AND CERTIFICATES

Colotitane is classified in family I Class 7a2 according to standard NM 03.3.009 (Tests carried out by LPEE CEMGI).

## STORAGE

The product can be stored for up to 2 years under good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

25 kg

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°10.

Edition : October 2021 by Colorado10/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001