



## DESCRIPTION

Water-based paint based on vinyl acetate resin, with a waxed concrete appearance.

## FIELD OF USE

For interior: DECOSOL can be applied indoors on FONDO DECOSOL on all types of new or old floors in good condition (raw, tiled, smoothed).

## TECHNICAL CHARACTERISTICS

- Aspect : pasty.
- Colors : According to our color chart.
- Spreading-rate : 7 to 8 m<sup>2</sup>/kg (approximately 5 m<sup>2</sup> / l) depending on the porosity of the support.
- Density : 1,40 +/- 0,05 at 25°C.
- Viscosity : 600 +/- 50 P at 25°C.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Preparation of the support in accordance with standard NFP74-201-DTU 59.1. Application temperature between 10 and 28 °C.

First coat application by roller or float in a very thin coat. This 1st layer must be smoothed with a stainless steel float. After a minimum of 4 hours of drying, the product can be ironed and smoothed. The second layer, always very thin, can be applied with increasing movements to obtain a smooth surface. Leave to dry for 8 hours, then polish with very fine steel wool. Finish with Decosol Varnish.

Application limit: Do not apply on condensing or frozen substrates, at temperatures below 5 °C, or at relative humidity above 70%.

## APPLICATION DETAILS OF USAGE

Dilution: ready to use.

## DRYING TIME

20 °C and at 0% humidity:

- \* Dust dry: 45 min.
- \* Dry: 2 hours.
- \* Interval between coats: 4 hours minimum.

## RECOMMENDED SYSTEM

### ■ INTERIOR

SYSTEM	NUMBER OF COATS
FONDO DECOSOL	2
DECOSOL	2
VERNIS DECOSOL (option)	2

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

2 L.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 103-1

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001