



DESCRIPTION

Thick wall plaster with a rough earth look.

FIELD OF USE

It is easy to apply and helps mitigate the effects of small irregularities in the bottoms.
It can be applied indoors on new or old walls in good condition.

TECHNICAL CHARACTERISTICS

- Aspect : Pasty product.
- Colors : According to our color chart.
- Spreading-rate : 1 m²/Kg (in one layer).
- Density : 1,58 +/- 0,01 at 25°C.
- Viscosity : 1400 +/- 200 poises at 25°C.
- Dry extract (% by weight) : 67 +/- 2%.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Apply with a float on a prepared dry, healthy and dust-free surface. Do not apply on wallpaper. Apply DECOTERRE using a metal float, making crossed, flexible and irregular movements to obtain a more or less structured appearance (with more or less relief).
Leave for 30 minutes, then lightly moisten your surface (about 2 m² at a time) with a sponge, and iron with a stainless steel float, crushing any extra thickness. Add some effects by scratching your surface in places with a wire brush. To better protect DECOTERRE on the outside, it is advisable to apply a coat of COLOPRIM as a finish.

APPLICATION DETAILS OF USAGE

Dilution: ready to use.

DRYING TIME

We advise you to make your part in one go to avoid possible nuances. Drying at 20 ° C and 60% humidity:
* Initial: 30 minutes.
* At heart: 48 hours

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505 or SP88	1
COLOMAT 99	1
COLOFONDO	1
DECOTERRE	1
COLOPRIM (Option)	1

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

7 Kg

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°101.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001