



## DESCRIPTION

Thick, textured decorative coating based on aqueous phase acrylic copolymers, containing quartz grains.

## FIELD OF USE

Particularly suitable for embellishing and protecting facades.  
High water vapor permeability, excellent water resistance.

## TECHNICAL CHARACTERISTICS

- Aspect : Pasty product, granite appearance and a natural mat.
- Colors: To be defined
- Spreading-rate : 1 to 1,5 m<sup>2</sup>/kg compliant with ISO 23811 (2009).
- Density : 1,68 +/- 0,05 à 25°C, Complies with NM ISO 2811-1 (2008).
- Viscosity : 1600 +/- 400 poises at 25° C (Brookfield).
- Dry extract (by weight) : 78 % ± 2 %.
- Dry film thickness : 2 to 3 mm.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Apply (without diluting) with a stainless steel float or coating knives to spread the product, and simultaneously bring out the desired decorative appearance using a special float.  
Application limit: Do not apply on condensing or frozen substrates at temperatures below 5 ° C, and above 35 ° C, nor at relative humidity above 80%.

## APPLICATION DETAILS OF USAGE

Dilution: Water.

## DRYING TIME

Drying at 20 ° C and 60% humidity:

- \* Dust free: 1h
- \* Dry: 4 hours.

## RECOMMENDED SYSTEM

SYSTEM	NUMBER OF COATS
COLOSHIELD PRIMER	1
DOREX	1

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

30 kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 66.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.  
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001