



DESCRIPTION

Enduiflex is a powder coating that traps moisture. It is based on cement, selected quarry products and water-repellent silvers. W3 rated

- * Block moisture.
- * Let the support breathe.
- * Can be covered by any coating or paint finish.
- * Even out surfaces and fill holes up to 1cm thick.

FIELD OF USE

All masonry supports, interior or exterior rough, dry or wet, such as cement, concrete, breeze block, brick, stone. The walls must be healthy and not oozing. ENDUIFLEX is classified W3 according to standard NE EN 1062-1.

TECHNICAL CHARACTERISTICS

- Color : White.
- Spreading-rate : 1.5 kg / m² and per mm of thickness

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Apply in 1 or 2 coats, depending on the desired thickness, with the plank to be coated. Apply a homogeneous thickness to the surface to be coated. To obtain a good effectiveness, apply at least 2mm of thickness in a regular way.
Do not apply at temperatures below 5 °C or above 40 °C. Do not apply to overheated or wet surfaces.
In dry and hot weather, moisten the surface to be coated before application.

APPLICATION DETAILS OF USAGE

Dilution:
Mix the product with +/- 30% water.
Mix the product well. Let stand 15 minutes.
Then mix again before application to have a homogeneous coating.

DRYING TIME

Interval between coats: 24 hours

RECOMMENDED SYSTEM (contact us)

■ INTERIOR / EXTERIOR :

SYSTEM	NUMBER OF COATS
ENDUITFLEX	2 (2mm minimum)
COLOPRIM or COLOFIX	1
FINISHING PAINT	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

5kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 166.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001