



## DESCRIPTION

Two-component epoxy paint floor covering Has great mechanical and chemical resistance.

## FIELD OF USE

Intended for the protection of concrete or cement supports for industrial use, in particular car parks, stores, workshops, etc.

## TECHNICAL CHARACTERISTICS

- Aspect : Brilliant.
- Colors : A choice.
- Spreading-rate : 3.8m<sup>2</sup>/L/100µm.
- Density : 1.3 ± 0,05.
- Volume-solids : 50 ± 2%.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## APPLICATION PROPERTIES

The 2 components are mixed in the following mass proportions: 4 base and 1 hardener.

- \* Maturation time: 10 min
- \* Mixture life: 4 hours,
- \*Application material: roller or spray air on a dry, dust-free surface.
- \*Application limit: Do not apply on condensing or frozen support, at temperature below 10 ° C, or at relative humidity above 70%.
- \*Support temperature: between 10 ° C and 40 ° C.

To carry out applications under conditions different (T<10°C and RH>70% as well as spaces closed without ventilation), apply our EPOXYDUR PLUS.

## APPLICATION DETAILS OF USAGE

Dilution: Thinner H303, D33 (5 to 15%).

## DRYING TIME

Drying at 20 ° C and 60% humidity

- \* Surface-dry : 1Hour
- \* Through-dry : 4 Hours
- \* Recoverable : 24 Hours

## RECOMMENDED SYSTEM

### ■ INTERIOR (Floor):

SYSTEM	NUMBER OF COATS
VERNIS BETONIX (option)	1
EPOXYDUR	2

\* Wall application possible.

## STORAGE

The product can be stored for up to 1 year under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

## PACKAGING

Base: 4kg, 16 kg  
Hardener: 1kg, 4 kg

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 33.

Edition : May 2023 by Colorado 05/23 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001