



DESCRIPTION

Matt paint based on vinyl emulsion for economical work.

FIELD OF USE

ITOVINYL + can be applied to interior substrates, such as cement plaster and plaster. It is intended for economic work.

TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Colors : Supplied in white, it can be tinted with our Tints 2000.
- Spreading-rate : About 4,5 to 5 m²/kg depending on the porosity of the support.
- Density : 1,72 +/- 0,05 at 25°C.
- Viscosity : 650 +/- 50 poises at 25°C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Itovinyl + is applied to interior substrates, such as cement plaster and plaster. It has good whiteness and coverage and is intended for economical work. They apply easily.

It is applied with a roller or possibly a brush. Generally, two coats are applied diluted according to the porosity of the support.

Application limit: Do not apply on condensing, frozen substrates, at temperatures below 5 ° C and / or relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution: up to 15% water.

DRYING TIME

- *Dust free: 15 min.
- *Dry: 1 hour.
- * Interval between coats: minimum 3 hours.

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX or FORMORAL (*)	1
SILENDUIT V805 or P66 ou P77	2
ITOVINYL+	2

(*) Depending on the support.

STORAGE

The product can be stored for up to 2 years under good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

1 kg, 5 kg, 10 kg 30 kg, 45 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 42.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001