



DESCRIPTION

PAINT-ALL is a satin acrylic water-based paint. PAINT-ALL is a 2 in 1 product: primer and finish. Interior Exterior.

FIELD OF USE

PAINT-ALL can be applied directly to different supports (earthenware, plastic, melamine, laminate, and old paintings, wood ...).

TECHNICAL CHARACTERISTICS

- Aspect : Satin.
- Color : White, it can be tinted with our Tints 2000.
- Spreading-rate: 12 m² / Kg per coat, conforms to ISO 23811 (2009).
- Density : 1,20 +/- 0,05 at 25°C, Complies with NM ISO 2811-1 (2008).
- Viscosity : 120 +/- 5 KU at 25°C, complies with ASTM D561 (1997).
- Gloss: 18 at 60 °, in accordance with standard NM ISO 2813 (2005).

SURFACE PREPARATION

The preparation must be done with the greatest care. Any surface to be painted must be clean, dry, non-greasy and not chipped. Poor preparation can lead to non-adherence of PAINT-ALL.

- Raw or new support:

Wood: Sand, dust. Exotic wood, degrease with acetone.

Iron : Degrease with acetone. Remove the rust and remove dust. Apply a coat of white rust inhibitor.

Non-ferrous metals : Sand with fine grit sandpaper, degrease and apply a coat of WASH PRIMER.

Earthenware and tiling : Degrease, wash off, rinse with clear water.

- Support already painted, in good condition :

Sand with fine grain and dust.

- Support already painted, in poor condition :

Scrape loose pulleys, sand and dust. If returning to the raw support, repeat the application of the raw supports.

- Plastic support:

Degrease, sand with a fine grain then remove dust. Considering the great variety of products available on the market, we advise you to carry out a prior adhesion test.

CONDITIONS AND METHODS OF APPLICATION

It is applied by roller or possibly by brush on clean, dry and dust-free bases in accordance with standard NF DTU 59.1.

Usually two coats are applied without dilution. Application limit: Do not apply on condensing, frozen substrates, at temperatures below 5 ° C and / or relative humidity above 70%.

APPLICATION DETAILS OF USAGE

Dilution: ready to use.

DRYING TIME

- * Dust dry: 30 min.
- * Dry: 45 minutes.
- * Interval between coats: minimum 6 hours.

RECOMMENDED SYSTEM (Consult us)

■ INTERIOR:

SYSTEM	NUMBER OF COATS
PAINT-ALL	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from direct sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

1 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N°192 .

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B: The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001