



## DESCRIPTION

PATENDUIT is a paste coating based on emulsion of vinyl copolymers.

## FIELD OF USE

Fills and masks surface roughness; Protects against the alkalinity of cement substrates. Applies easily and flexibly while drying quickly.  
PATENDUIT can be applied to all cement, fiber cement, plaster and wood substrates.

## TECHNICAL CHARACTERISTICS

- Aspect : Matt.
- Spreading-rate : \* Coating: 2 to 3 m<sup>2</sup>/Kg.  
\* Raking : 3 to 4 m<sup>2</sup>/Kg.
- Density : 1,75 +/- 0,05 Kg/L at 25°C.
- Dry extract (by weight) : 74 % +/- 2 %.
- Viscosity : 3600 +/- 200 poises with a Brookfield viscometer at 25 °C.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## CONDITIONS AND METHODS OF APPLICATION

Recommended material: Coating knife.  
Application limit: Do not apply on condensing or frozen substrates, at temperatures below 5 °C, or at relative humidity above 70%.

## APPLICATION DETAILS OF USAGE

Dilution: Ready to use.

## DRYING TIME

Drying at 20 °C and 60% humidity:  
\*Dust free: 30 min +/- 10 min.  
\* Dry: 1 hour +/- 10 minutes.

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

25kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°11.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.  
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001

[www.colorado.ma](http://www.colorado.ma)