



## DESCRIPTION

PRIMAIRE EPOXY MS is a two-component, low viscosity epoxy varnish with good penetrating properties.

## FIELD OF USE

It is intended for the protection of concrete or cement supports for industrial use, particularly appreciated as an undercoat of epoxy paint and for floors. Primaire Epoxy MS used as a protective varnish for epoxydur.

## TECHNICAL CHARACTERISTICS

- Aspect : Brillant.
- Colors: Transparent.
- Spreading-rate : 13 m<sup>2</sup>/kg/30μm.
- Density : 0.98 ± 0,05.
- Volume-solids : 39± 2%.

## SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

## APPLICATION PROPERTIES

The 2 components are mixed in the following mass proportions: 4 base and 1 hardener.

- \* Maturation time: 10 min;
- \* Pot life of the mixture: 4 hours;
- \* Application material: roller, brush or spray air;
- \* Application limit: Do not apply to support condensing or frozen, by temperature below 5 ° C, nor by relative humidity above 70%
- \* Support temperature: between 5 ° C and 40 ° C.

## APPLICATION DETAILS OF USAGE

Dilution: Thinner H303 ; H5250 or D33 (20-30%).

## DRYING TIME

- Drying at 20 ° C and 60% humidity
- \* Surface-dry : 1.5 Hour
  - \* Through-dry : 6 - 8 Hours
  - \* Recoverable : 24 Hours.

## STORAGE

The product can be stored for up to 1 year in good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

## PACKAGING

Base: 16kg; 4kg.  
Hardener: 4kg; 1kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 90.

Edition : March 2024 by Colorado 03/24 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001, ISO 45001 and ISO 27001