



## DESCRIPTION

ROVANA is a lime-based mineral coating.  
Decorative product with a natural effect.

## FIELD OF USE

Recommended for application on interior walls.

## TECHNICAL CHARACTERISTICS

- Aspect : Pasty product.
- Color : White.
- Spreading-rate : About 1kg / m<sup>2</sup> (in 1 coat), in accordance with ISO 23811 (2009) (may vary depending on roughness, porosity and absorption of the substrate and the method of application).
- Density : 1,65 Kg/L +/- 0,05 at 25° C, Complies with NM ISO 2811-1 (2008).
- Viscosity : 860 +/- 50 Poise at 25° C (Brookfield).

## SURFACE PREPARATION

In accordance with the professional standard (DTU 59.1): substrates must be clean, dry, sound, hard and cohesive

## CONDITIONS AND METHODS OF APPLICATION

Do not apply at temperatures below 5 ° C and above 35 ° C.  
Relative humidity should be <65%.  
It is advisable to work with the same batch number on the entire surface to be painted.

## APPLICATION DETAILS OF USAGE

Processing equipment: stainless steel float and special brush  
On a previously prepared support, apply a layer of COLOFONDO and leave to dry for 4 hours.  
The product is applied in 1 layer:  
Apply ROVANA with a stainless steel float on the wall, before it dries, finish with the appropriate tools, according to the desired effect. While the product is still wet, use a special brush to create irregular and wavy marbling in an oblique direction, from top to bottom and from bottom to top.  
After 30 - 40 minutes at 20 ° C, spray water on the wall using a sprayer. This will make it easier to smooth ROVANA with a stainless steel float.  
After 24 hours at 20 ° C decorate with a sponge, using the VERNIS finish which must be applied in two coats. Wait 4 hours at 20 ° C after each passage.

## DRYING TIME

Around 24 hours to 48 hours depending on thickness.

## RECOMMENDED SYSTEM

SYSTEM	NUMBER OF COATS
COLOFONDO	1
ROVANA	1
ROVANA VARNISH	2

## STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

## PACKAGING

5 kg, 20 kg.

## HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°258.

Edition : October 2021 by Colorado 10/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.  
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001

[www.colorado.ma](http://www.colorado.ma)