



DESCRIPTION

STOP INSECTES is a paint based on acrylic copolymers in aqueous phase for interior and exterior. STOP INSECTES kills insects, flies, mosquitoes, cockroaches, ants, mites on contact.

Depending on the type of insects, the contact time necessary for their deaths varies from 30 minutes to 4 hours.

STOP INSECTES is approved according to the CEB 135 method. STOP INSECTES is effective for up to two years.

FIELD OF USE

STOP INSECTES can be applied to interior and exterior masonry cladding; woodwork and plaster. STOP INSECTES contributes to improving hygiene and limiting the presence of allergens in the home. It dries quickly, it is odorless and does not flour. It is washable and is very easy to apply.

TECHNICAL CHARACTERISTICS

- Aspect : Mätt.
- Colors : Delivered in white, it can be tinted with our Tints 2000. (Maximum 2% dye).
- Spreading-rate : $\pm 6 \text{ m}^2/\text{Kg}$ depending on the porosity of the support. Complies with ISO 23811 (2009).
- Density : $1,64 \pm 0,05$ at 25°C . complies with NM ISO 2811-1 (2008).
- Dry extract (by weight) : $72\% \pm 2\%$.
- Viscosity : 380 - 460 poises with a Brookfield viscometer at 25°C .

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

STOP INSECTES can be applied with a roller or brush without any risk of reworking or joining.

Application limit: Do not apply on condensing or frozen substrates at temperatures below 5°C , and above 35°C , nor at relative humidity above 80%.

APPLICATION DETAILS OF USAGE

Dilution of 10 to 15% water.

DRIYING TIME

At 20°C and 65% humidity:

*Dust free: 15 min

*Dry: 30 min

Recoatible after 3 hours minimum.

RECOMMENDED SYSTEM

EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10	1
COLOPRIM or COLOFIX	1
STOP INSECTES	2

INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT Extra B505 or SP88	2
STOP INSECTES	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from direct sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

5 Kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N°199.

Edition : April 2021 by Colorado 04/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.

This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001