



DESCRIPTION

Washable high-decoration paint that has an old-fashioned marbled decorative appearance, and a TADELLAKT effect. Suitable for all exposed spaces: exterior facades, kitchens and bathrooms thanks to its resistance to mold.

FIELD OF USE

Recommended for application on exterior and interior walls.

TECHNICAL CHARACTERISTICS

- Aspect : Pasty product.
- Colors : White, colors: see catalog.
- Spreading-rate : 3 to 4 m² / kg (2 Layers).
- Density : 1,58 +/- 0,05 at 25°C.
- Viscosity : 1000 +/- 200 poises at 25°C.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

If the support is wet; remove the source of moisture and apply a water-repellent coating with an impregnation varnish.

- * On a previously prepared substrate, apply a medium, even coat using a lacquer roller. Before the product dries, using a triangular spatula, lightly crush in all directions. Work in areas of 1 to 2 m² (without risk of rework).
- * Leave to dry for about 7 hours, then by simply scraping with a knife remove any roughness.
- * Apply without dilution a second coat by working directly with a plastic or stainless steel trowel.
- * Wait 3 to 4 hours and with the plastic smoother accentuate the contrast of colors by simple smoothing.

APPLICATION DETAILS OF USAGE

Dilution: Product ready to use, can be diluted with water.

DRYING TIME

- * 1st layer: 12h
- * 2nd layer: 4h

RECOMMENDED SYSTEM

■ INTERIOR

SYSTEM	NUMBER OF COATS
COLOPRIM or COLOFIX	1
COLENDUIT EXTRA B505	2
COLOVINYL 600 EXTRA	1
STUCCO KSOUR	2

■ EXTERIOR

SYSTEM	NUMBER OF COATS
ENDUIT FACADE P20 or P10	1
COLOPRIM or COLOFIX	1
COLOVINYL 600 EXTRA	1
STUCCO KSOUR	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

1 kg, 5 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N° 21.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001