



DESCRIPTION

TOUFLEX is a satin waterproofing paint, based on elastic fiber copolymers.

FIELD OF USE

Thanks to specially selected additives, TOUFLEX is intended for accessible terraces, roofs and facades. Has excellent flexibility and good weather resistance. It is algacide and fungicide.

*Touflex is mainly intended for accessible terraces. However, we advise you to be careful if you move objects. Do not drag them onto the terrace.

TECHNICAL CHARACTERISTICS

- Aspect : Satin.
- Colors : Brick red, Grey, and White.
- Density : $1,28 \pm 0,05$, to comply with the standard NM ISO 2811-1 (2008).
- Viscosity : 550 ± 50 P at Brookfield at 25°C.
- Spreading-rate : 1,4 to 2,1 m²/kg depending on the condition of the substrate.

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

- *Application material: Brush, roller or spray.
- *Instructions for use: On porous surfaces, dilute the 1st coat up to 50% with water then apply 2 coats without dilution. Otherwise, apply directly 2 or 3 crossed coats without dilution until a minimum thickness of 1 to 1.2 mm is obtained for a good seal.
- *Application limit: Do not apply on condensing or frozen substrates at temperatures below 5 ° C, and above 35 ° C, nor at relative humidity above 80%.

APPLICATION DETAILS OF USAGE

Dilution: With water.

DRIYING TIME

Drying at 20 ° C and 60% humidity:
 * Dry: 6 to 8 hours.
 * Recoatable: 24 hours.

RECOMMENDED SYSTEM

EXTERIOR :

SYSTEM	NUMBER OF COATS
TOUFLEX (diluted to 50%)	1
TOUFLEX (without dilution)	2

STORAGE

The product can be stored for up to 2 years in good storage conditions away from direct sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

5 kg, 20 kg.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N° 256.

Edition : November 2021 by Colorado 11/21 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001