



DESCRIPTION

ROVANA varnish is applied as a finish to the ROVANA system. ROVANA varnish enhances the shine of ROVANA and gives it a metallic finish. ROVANA VARNISH gives the applied surface better washability.

FIELD OF USE

Protective or decorative varnish for the ROVANA system.

TECHNICAL CHARACTERISTICS

- Aspect : Pearl and metallic.
- Color : Silver and M.A.T.
- Spreading-rate : +/- 8m²/L , compliant with ISO 23811 (2009).
- Density : 1,00 +/- 0,05 , complies with NM ISO 2811-1 (2008).
- Viscosity : 100+/-5Ku at 25° C (Krebs).

SURFACE PREPARATION

The work must be done in accordance with standard NF DTU59.1 and will be carried out with the greatest care.

CONDITIONS AND METHODS OF APPLICATION

Do not apply in a draft.
When using multiple batches, it is recommended to mix the different batches together to avoid slight differences in shade.
ROVANA varnish must be applied between + 5 ° C and + 35 ° C.

APPLICATION DETAILS OF USAGE

ROVANA SILVER VARNISH can be used in silver or tinted with M.A.T on ROVANA.
Application using a sponge or a special float on ROVANA plaster to create the desired effect.

DRYING TIME

Drying at 20 ° C and 0% humidity :
* Dust Free: 30 min
* Dry : 4 hours.
* Recoatable: 4 hours.

RECOMMENDED SYSTEM

SYSTEM	NUMBER OF COATS
FONDO	1
ROVANA	1 or 2
VERNIS ROVANA	2 or 3

STORAGE

The product can be stored for up to 2 years in good storage conditions away from sunlight, it is nevertheless recommended to shake the product before use.

PACKAGING

800 ml.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed on the safety data sheet N°270.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted.
This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001