



DESCRIPTION

WASH PRIMER is an anti-torsion bonding primer for all metals and especially aluminum and galvanized steel. Catalyzed acid.

FIELD OF USE

Has excellent adhesion and resistance to corrosion in industry and bodywork, inside and out.

TECHNICAL CHARACTERISTICS

- Aspect : Matt, smooth.
- Colors: Yellow, greenish.
- Spreading-rate : 15-20 m² /L/10 µm.
- Density : 0.90 +/- 0,05 at 25°C.

SURFACE PREPARATION

The product is applied in one coat with a brush or gun (pneumatic) to the well prepared, sanded, dry, degreased, brushed and dusted substrate.

Application limit: Do not apply on condensing or frozen support, at temperature below 5 ° C, or at relative humidity above 70%.

CONDITIONS AND METHODS OF APPLICATION

The 2 components are mixed in the following volume proportions:

9 basic and 1 Catalyst.

Maturation time: Can be used immediately after mixing.

Mixture life: 8 hours.

RECOMMENDED SYSTEM

Wash Primer can be overcoated with all types of solvent based undercoats and finishes within 12 hours of application.

APPLICATION DETAILS FOR USAGE

Dilution: Ready to use.
Cleaning of tools with D33 or D55.

DRYING TIME

Drying at 20 ° C and 60% humidity
*Dry: 10 min.
*Recoatable: 20 minutes

STORAGE

The product can be stored for up to 1 year under good storage conditions away from sunlight and frost in its original closed packaging. It is nevertheless recommended to shake the product before use.

PACKAGING

Base : 900 mL- 4.5L.
Catalyst : 100 mL- 500 mL.

HEALTH & SAFETY

Health and safety information and precautions for use are detailed in the safety data sheet N°157.

Edition : July 2020 by Colorado 07/20 (DC28 D).

N.B : The purpose of this technical data sheet is to provide information on the properties of our product. The information contained therein is based on our current knowledge of tests carried out with a constant concern for objectivity according to the conditions of use in accordance with standards or DTU in force; However, the information cannot replace an appropriate description and the state of the funds to be painted. This descriptive technical sheet cancels and replaces any sheet relating to the same product. The above technical data does not imply acceptance of the guarantees. Close the pot tightly after use. Help preserve the environment by not disposing of waste in the drains or household waste. Please return your empty jar to a recycling center. For your unused product, please contact your local authorities for information on disposal and collection.

COLORADO is certified ISO 9001, ISO 14001 and ISO 45001